

ROTOBALE COMPACTION SOLUTIONS INC.

Rotobale RC Series Self Contained Compactors

Rotobale has used its' 40 years of manufacturing waste and recycling equipment to design our RC Series Self Contained Compactors with the most compaction in the industry; utilizing our low ram face design combined with 16" ram penetration more waste and recyclables get packed into the container, making it the most cost-efficient compactor by reducing your trips to the landfill.

Product Features:

- 16" RAM PENETRATION within the container, the "most in the industry"
- RAM DWELLS AGAINST THE LOAD increasing compaction
- SOLID STEEL BUBBLE DOOR for more compaction capacity
- NEWLY DESIGNED "NO LEAK" door gasket
- 4.5" CROSS CYLINDER DESIGN ideal for tight spaces allowing for a steeper chute
- 43" FEED HEIGHT designed for easy accessibility
- MANUFACTURER'S SAFETY DECLARATION

Benefits:

- Reduces haulage costs as the RC Series of Self Contained Compactors pack more than the industry standard
- Eliminates liquid/waste spillage, leakage and odour utilizing our liquid tight seal
- Provides a safer and cleaner environment as there is NO ACCESS to the container
- Increase waste and recycling capacity up to 35% with our 44 yard self contained compactor

Ideal For: Supermarkets, Restaurants, Plaza's, Hotel's and Manufacturing Plants

Canada's leading manufacturer of waste compaction and recycling equipment











ROTOBALE COMPACTION SOLUTIONS INC.

7232 Arthur Road #5 West Kenilworth, ON NOG 2E0

T: (519) 323.3673

TF: (800) 565.8027

F: (519) 323.3816 www.rotobalecompaction.ca

MODEL "RC" SELF CONTAINED COMPACTOR GENERAL SPECIFICATIONS

		20 CU YD	30 CU YD	35 CU YD	40 CU YD	44 CU YD	
Dimensions							
Overall Length Overall Height Overall Width (container rear) Overall Width (container front) Chargebox WxLxD	A B C D ExFxG	204" 100" 102" 88" 60"x43"x28"	250" 100" 102" 88" 60"x43"x28"	274" 100" 102" 88" 60"x43"x28"	300" 100" 102" 88" 60"x43"x28"	324" 100" 102" 88" 60"x43"x28"	
Feed Height	Н	43"	43"	43"	43"	43"	
Performance Characterstics							
Operational Compaction Force Maximum Compaction Force Ram Penetration (within container)		63,600 lbs 76,320 lbs 16"					
Electrical / Hydraulic Specifications	;						
Electrical Motor Pump Capacity Cycle Time		10 / 5 HP 10.8 / 5.4 gpm 45s / 90s	10 / 5 HP 10.8 / 5.4 gpm 45s / 90s	10 / 5 HP 10.8 / 5.4 gpm 45s / 90s	10 / 5 HP 10.8 / 5.4 gpm 45s / 90s	10 / 5 HP 10.8 / 5.4 gpm 45s / 90s	
Voltage		To suit customers needs					
Electrical Control Voltage Normal Pressure		110VAC 2000 psi					
Maximum Pressure Hydraulic Cylnder		2400 psi (2) 4.5"					

SPECIFICATIONS SUBJECT TO CHANGE WITHIOUT NOTICE TO ACCOMMODATE EQUIPMENT IMPROVEMENTS



ROTOBALE COMPACTION SOLUTIONS INC.

Rotobale RC Series Self Contained Compactors

Proud Canadian Manufacturer **Since 1968**













